

NOTES:


1. MATTING MATERIAL SHALL BE DOUBLE SIDED GEOCOMPOSITE, GEONET CORE WITH NON-WOVEN COVERING (SUCH AS TENAX TENDRAIN 770/2) OR APPROVED EQUIVALENT.
2. RPM SHALL BE INSTALLED BY A CERTIFIED ARBORIST.
3. TO BE USED FOR DESIGNATED TEMPORARY CONSTRUCTION ACCESS AND STOCKPILE AREAS.
4. MATTING SHALL BE PLACED ON 4-6" WOOD CHIP MULCH UNLESS OTHERWISE DIRECTED.
5. FOR HEAVY TRAFFIC AREAS, MATTING SHALL BE COVERED WITH 6-8" WELL GRADED CRUSHED AGGREGATE. ADDITIONAL LAYERS OF GEOTEXTILE MAY BE NEEDED.

COVER MATTING WITH AGGREGATE FOR HEAVY TRAFFIC USE

ROOT PROTECTION MATTING ANCHORED BY 12" LANDSCAPE NAILS @ 3' AVERAGE SPACING.

4-6" WOOD CHIP MULCH

ROOT PRUNE PER PLAN (SEE DETAIL)



TEMPORARY ROOT PROTECTION MATTING WITHIN CRZ

311300.7NS

NOT TO SCALE

